

# The V-series Eletta Flow Monitor

with one adjustable  
switchpoint



**Eletta flow**

when you want to know



### GL series

The Pipe Section is constructed of copper alloy and fitted with BSP/ NPT threads from 15 mm to 40 mm (1/2"–1 1/2").

### Benefits of the V-series

- Rugged and sturdy design
- Uses proven differential pressure technique
- Economical alternative to more expensive flow meters
- Liquids and gases can be monitored
- Dependable and economical
- One SPDT micro switch for adjustable flow alarm
- Insensitive to magnetic fields

### Important applications and product features

- Monitoring flows in cooling and lubricating circuits
- Antifreeze protection of heat pump systems
- Dry out protection
- Starting and stopping pump motors
- Shows flow without external power
- Low cost solution for difficult flow applications
- Interchangeable control units to fit all pipe sections
- Not affected by static pressure



### FA series

The Pipe Section has a flanged (wafer) process pipe connection and the material is bronze from 15 mm up to size 40 mm (1/2"–1 1/2") and epoxy polyester coated cast iron in sizes 50 mm to 400 mm (2"–16").



### GSS series

The Pipe Section is made from Stainless Steel and comes with BSP/NPT threads in size 15, 20 and 25 mm (1/2", 3/4" and 1").



### FSS series

The Pipe Section comes in stainless steel and has the same "fit between flanges" (wafer) execution as the -FA series and process connections from 15 mm to 500 mm (1/2"–20").

## The V-series Flow Monitor

**The Eletta Flow Monitor's function is based on the proven and dependable differential pressure principle. This is perhaps the oldest and most widely used principle for flow metering, mainly because of its simplicity and its relatively low cost.**

The Eletta V-series Flow Monitor is used to control flow of liquids and gases in pipes from 15 mm to 500 mm. Through the adjustable SPDT micro switch it is possible to set one low or high flow alarm to protect expensive equipment in various piping systems. The switching point is highly repeatable, within <2%. The Flow Monitor is insensitive to surrounding magnetic fields and it combines the long-standing proven mechanical function with outstanding reliability. Together with an exceptionally sturdy and robust design, this makes it extremely well suited for difficult environments.

The V-series comes in two measuring ratios designated **V1** and **V15**, which means that the **V1** has a flow measuring span of 1:2 and the **V15** has a span of 1:5.

Like all Eletta Flow Monitors the V-series can monitor both liquids and gases.

## Modular design

All the Eletta Flow Monitors including the V-series can be fitted to any of the various Eletta Flow Monitor Pipe Sections to suit your application.

The Instrument consists of two parts mainly, i.e. the Pipe Section and the Control Unit. The Pipe Section is the part that is to be mounted in the process pipe and the Control Unit is mounted directly (standard) or remote to the Pipe Section.

As the Control Unit is pre-calibrated before leaving our production facilities, you can change pipe sections to fit other dimensions and materials than originally ordered without recalibration.

The Control Unit contains the micro switch which can be set to trip anywhere within the measuring range.

The Pipe Sections come in Copper alloy, Stainless Steel, Cast Iron and sizes from DN 15/PN16 (ANSI 1/2"/150 lbs) up to DN 500/PN16 (ANSI 20"/150 lbs). The V-series Control Unit can also be used to supplement an already installed Eletta Flow Monitor such as the S-, A- or R-series even after the installation.



## Specifications V-series



<b>Flow range:</b>	0,4 – 25 000 l/min (liquid)
<b>Min. flow:</b>	V1: 50% of the full scale flow range V15: 20% of the full scale flow range
<b>Wetted materials:</b>	Copper alloy, epoxy painted cast iron. Seaworthy stainless steel 904L, stainless steel, 316
<b>Rubber parts:</b>	Nitrile (HNBR), EPDM and Fluorinated rubber (FPM)
<b>Max. pressure:</b>	16 bar (232 PSI)
<b>Standards:</b>	PN 16/ANSI 150 lbs
<b>Max. temp. Control Unit:</b>	90°C standard, 120°C optional.
<b>Max. temp. Pipe Section:</b>	-GL and -FA: 120°C (248°F) -GSS, -FSS: 250°C (482°F)
<b>Enclosure:</b>	IP43 (NEMA3R) std. IP65 (NEMA4) option
<b>Process Connection:</b>	DN 15-40, BSP/NPT thread DN 15-500 DIN/ANSI flange (wafer)
<b>Alarm:</b>	V1 and V15 have one (1) micro switch contact, independently adjustable within the ordered Flow range
<b>Micro switch spec:</b>	Contact surfaces are silver plated as standard. Type: SPDT Hystereses: 10% Rated voltage: 480 VAC/15A Breaking current: 15@125, 250, 480 VAC Resistive load: 2A@30 VDC 0,4A@125 VDC 0,2A@230 VDC
<b>Repeatability:</b>	< 2% actual
<b>CE-approvals:</b>	The Eletta Flow Monitors conforms with the EU directive for low voltage no: 72/23/EEC (EN 60 204-1, Part 1.) and Electromagnetic compatibility according to the directive 89/336/EEC (EN 50081-1 and 50082-2) Complies with applicable parts in PE-Directive 97/23/EG

### Eletta Flow Monitors

The name Eletta has become synonymous with flow monitoring in many industries world wide where the Products are appreciated for their sturdy and robust design.

Eletta Flow Monitors are of our own proprietary design and our manufacturing as well as the whole company is certified to ISO 9001 and ISO 14000 quality standards.

We export our Products all over the world and we have Authorized Distributors in most European countries, Australia, South Africa, India, Japan and USA.

### Find out more

In our technical leaflets and manuals you will find full details of the design, pressure drop graphs, measuring ranges and dimensional drawings. We welcome you to our at all time updated web site at [www.eletta.com](http://www.eletta.com) for the most recent and accurate information about Eletta and our Products. At this site you can find most of the documentation on down-loadable files. Whatever your request for information is, our e-mail address: [info@eletta.com](mailto:info@eletta.com) is the fastest way to get in contact with our Customer Support and technical department. Of course, your local Eletta Distributor, whose address you can find in our homepage, can assist you in most cases.

# ELETTA

— FLOW MONITORS —

**Eletta Flow AB**

Box 5084, SE-141 05 Kungens Kurva, Sweden  
Tel. +46 8 603 07 70 • Fax. + 46 8 646 10 40

[info@eletta.com](mailto:info@eletta.com)  
[www.eletta.com](http://www.eletta.com)

# Measuring Ranges

## Eletta Flow Monitors

D2, V1, S02, S2, R2 and A2			
Dim. DN		lit/min	MCx(S2)
1/2" DN 15	GL,GSS FA, FSS	0,4 – 0,8	0,1
		0,6 – 1,2	0,15
		1 – 2	0,25
		1,6 – 3,2	0,4
		2 – 4	0,5
		2,4 – 4,8	0,6
		3,2 – 6,4	0,8
		4 – 8	1
		6 – 12	1,5
		8 – 16	2
		10 – 20	2,5
		12 – 24	3
16 – 32	4		
3/4" DN 20	GL,GSS FA, FSS	4 – 8	1
		6 – 12	1,5
		8 – 16	2
		10 – 20	2,5
		12 – 24	3
		16 – 32	4
20 – 40	5		
1" DN 25	GL,GSS FA, FSS	8 – 16	2
		10 – 20	2,5
		12 – 24	3
		16 – 32	4
		24 – 48	6
		36 – 72	9
40 – 80	10		
	FA, FSS	50 – 100	12,5
1 1/4" DN 32	FA, FSS	20 – 40	5
		28 – 56	7
		40 – 80	10
		60 – 120	15
		80 – 160	20
1 1/2" DN 40	GL, FA, FSS	20 – 40	5
		28 – 56	7
		40 – 80	10
		60 – 120	15
		80 – 160	20
	FA, FSS	100 – 200	25
2" DN 50	FA, FSS	40 – 80	10
		60 – 120	15
		80 – 160	20
		120 – 240	30
		160 – 320	40
2 1/2" DN 65	FA, FSS	60 – 120	15
		80 – 160	20
		120 – 240	30
		160 – 320	40
		240 – 480	60
		280 – 560	70
3" DN 80	FA, FSS	120 – 240	30
		160 – 320	40
		240 – 480	60
		320 – 640	80
		400 – 800	100
4" DN 100	FA, FSS	160 – 320	40
		280 – 560	70
		400 – 800	100
		600 – 1200	150
		700 – 1400	175
5" DN 125	FA, FSS	400 – 800	100
		600 – 1200	150
		800 – 1600	200
		1000 – 2000	250
6" DN 150	FA, FSS	600 – 1200	150
		800 – 1600	200
		1200 – 2400	300
		1400 – 2800	350
		1500 – 3000	375
8" DN 200	FA, FSS	800 – 1600	200
		1200 – 2400	300
		1600 – 3200	400
		2400 – 4800	600
		2500 – 5000	625
10" DN 250	FA, FSS	1600 – 3200	400
		2000 – 4000	500
		3200 – 6400	800
		4000 – 8000	1000



D5, V15, S05, S25, R5 and A5			
Dim. DN		lit/min	MCx(S25)
1/2" DN 15	GL,GSS FA, FSS	0,4 – 2	0,4
		1 – 5	1
		2 – 10	2
		4 – 20	4
		6 – 30	6
		8 – 40	8
3/4" DN 20	GL, GSS FA, FSS	4 – 20	4
		6 – 30	6
		8 – 40	8
		15 – 75	15
1" DN 25	GL, GSS FA, FSS	6 – 30	6
		12 – 60	12
		16 – 80	16
		24 – 120	24
	FA, FSS	30 – 150	30
1 1/4" DN 32	FA, FSS	8 – 40	8
		20 – 100	20
		40 – 200	40
		50 – 250	50
1 1/2" DN 40	GL, FA, FSS	8 – 40	8
		20 – 100	20
		40 – 200	40
		60 – 300	60
2" DN 50	FA, FSS	20 – 100	20
		40 – 200	40
		70 – 350	70
		100 – 500	100
2 1/2" DN 65	FA, FSS	20 – 100	20
		50 – 250	50
		100 – 500	100
		160 – 800	160
3" DN 80	FA, FSS	40 – 200	40
		80 – 400	80
		160 – 800	160
		240 – 1200	240
4" DN 100	FA, FSS	80 – 400	80
		160 – 800	160
		250 – 1250	250
		400 – 2000	400
5" DN 125	FA, FSS	100 – 500	100
		200 – 1000	200
		400 – 2000	400
		600 – 3000	600
6" DN 150	FA, FSS	200 – 1000	200
		400 – 2000	400
		600 – 3000	600
		900 – 4500	900
8" DN 200	FA, FSS	400 – 2000	400
		600 – 3000	600
		1000 – 5000	1000
		1500 – 7500	1500
10" DN 250	FA, FSS	600 – 3000	600
		1000 – 5000	1000
		1600 – 8000	1600
		2400 – 12000	2400

MC = Measuring Constant



It is possible to order a lower measuring range than indicated



FLOW MONITORS

Eletta Flow AB

Box 5084, SE-141 05 Kungens Kurva, Sweden  
Tel. +46 8 603 07 70 • Fax. + 46 8 646 10 40  
info@eletta.com • www.eletta.com

	<p>Unit 19, 15 - 23 Kumulla Road, Miranda NSW 2228.                  T: 02 9542 8977; F: 02 9542 7978; E: HELP@controlcomponents.com.au</p>	
---	---	---

Sr. No.	Specify the serial number of existing unit if it is being replaced	
Customer Name		
CCPL Quote		






Media/Fluid		
1	Type	Water, Oil, Gas etc. (Also, specify name of media, if applicable)
	Viscosity	cSt @ °C
	Density	
	Pressure	Operating pressure (refer data sheet for max. pressure)
	Temperature	Operating temperature (refer data sheet for max. temp.)


Control Unit		
2	Type & Turn-down Ratio	M3 or A2 / A5 or R2 / R5 or S2 / S02 / S25 / S05 or V1 / V15 or D2 / D5
	Enclosure	IP43 (NEMA 3R) / IP65 (NEMA 4)

Pipe Section		
3	Material	Brass (GL), Cast Iron wafer (FA) or SS (GSS & FSS)
	Connection	Thread (GL & GSS) or Wafer (FA & FSS) (DIN / ANSI)

Process connection		
4	Size	Select standard sizes from the respective data sheet (DN)

Measuring range		
5	Standard	Select a standard range from the respective data sheet (L/min)
	Special	Specify range within max. & min. related to turn-down. Price adder applies for special range calculations. (L/min)

Installation		
Facing / looking at the dial please fill in the correct flow direction: (A/B/C/D/E/F)		
6		A = Left to Right Flow
		B = Right to Left flow
		C = Up to Down flow with dial on right side of pipe
		D = Down to Up flow with dial on Right side of pipe
		E = Up to Down flow with dial on Left side of pipe
		F = Down to Up flow with dial on Left side of pipe

<p><b>For replacements, provide details from label of existing unit or a photo of label as shown to the right</b></p>	
---	--